

Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 04/03/2019

Revision date: 05/13/2021

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form	: Mixture
Product name	: Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix
Synonyms	: Mortar Mix Type O, N, S and M. Colored Mortar Mix Type O, N, S, M
Product code	: Not available

1.2. Recommended use and restrictions on use

Use of the substance/mixture	: Binder used for masonry, brick or block and other building and construction applications
------------------------------	--

1.3. Supplier

Manufacturer

Longleaf Packaging, LLC
621 Good Farm Rd.
Vance, SC 29163 - USA
T +1-803-857-8086

1.4. Emergency telephone number

Emergency number	: CHEMTREC (800) 424-9300
------------------	---------------------------

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin Irrit. 2
Eye Dam. 1
Carc. 1A
STOT SE 3

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: Causes skin irritation
Causes serious eye damage
May cause respiratory irritation
May cause cancer

Precautionary statements (GHS US)

: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust, fume, gas, mist, spray, vapors.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear eye protection, face protection, protective clothing, protective gloves.
If exposed or concerned: Get medical advice/attention.
If on skin: Wash with plenty of water
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing
Call a poison center or doctor if you feel unwell
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Immediately call a poison center or doctor
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Cement, portland, chemicals	(CAS-No.) 65997-15-1	80 - 100
Calcium oxide	(CAS-No.) 1305-78-8	≤ 70
Limestone (Calcium Carbonate)	(CAS-No.) 1317-65-3	≤ 60
Magnesium oxide (MgO)	(CAS-No.) 1309-48-4	≤ 10
Iron oxide (Fe ₂ O ₃)	(CAS-No.) 1309-37-1	≤ 10
Gypsum (Ca(SO ₄).2H ₂ O)	(CAS-No.) 13397-24-5	2 - 7
Quartz	(CAS-No.) 14808-60-7	0.1 - 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact : Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
- Symptoms/effects after eye contact : Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet. Contact with water will generate considerable heat.

Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Metal oxides.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Pick up large pieces, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Minimize generation of dust. The use of a HEPA vacuum may be acceptable.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Do not get in eyes, on skin, or on clothing. Do not breathe gas, fumes, vapour or spray. Use good housekeeping practices during storage, transfer, handling, to avoid excessive dust accumulation. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Protect from moisture. Keep away from food, drink and animal feeding equipment and food products. Store in a dry, cool and well-ventilated place. Keep from freezing.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Cement, portland, chemicals (65997-15-1)		
ACGIH	Local name	Portland cement
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
ACGIH	Remark (ACGIH)	Pulm func; resp symptoms; asthma
ACGIH	Regulatory reference	ACGIH 2017
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
OSHA	OSHA PEL (TWA) (ppm)	50 mppcf
OSHA	Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.

Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Cement, portland, chemicals (65997-15-1)		
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
IDLH	US IDLH (mg/m ³)	5000 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Limestone (Calcium Carbonate) (1317-65-3)		
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Magnesium oxide (MgO) (1309-48-4)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (fume, total particulate)
IDLH	US IDLH (mg/m ³)	750 mg/m ³ (fume)
Calcium oxide (1305-78-8)		
ACGIH	Local name	Calcium oxide
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
ACGIH	Remark (ACGIH)	URT irr
ACGIH	Regulatory reference	ACGIH 2017
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA
IDLH	US IDLH (mg/m ³)	25 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	2 mg/m ³
Gypsum (Ca(SO₄).2H₂O) (13397-24-5)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m ³)	50 µg/m ³
OSHA	Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m ³ / (%SiO ₂ +2)) for mg/m ³ . CAS No. source: eCFR Table Z-1.
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
Iron oxide (Fe₂O₃) (1309-37-1)		
ACGIH	Local name	Iron oxide (Fe O)
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (respirable particulate matter)
ACGIH	Remark (ACGIH)	Pneumoconiosis
ACGIH	Regulatory reference	ACGIH 2018

Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Iron oxide (Fe ₂ O ₃) (1309-37-1)		
OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
OSHA	Regulatory reference (US-OSHA)	OSHA
IDLH	US IDLH (mg/m ³)	2500 mg/m ³ (dust and fume)
NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (dust and fume)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear chemically resistant protective gloves.

Eye protection:

Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Color	: Various
Odor	: None
Odor threshold	: No data available
pH	: > 12 (in water)
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 2.8-3.0
Solubility	: Negligible. Water: < 1 %
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available

Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal storage conditions. Keep dry in storage.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials. Moisture. Keep from freezing.

10.5. Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Metal oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Magnesium oxide (MgO) (1309-48-4)

LD50 oral rat	3870 mg/kg
---------------	------------

Iron oxide (Fe₂O₃) (1309-37-1)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

Skin corrosion/irritation	: Causes skin irritation. pH: > 12 (in water)
Serious eye damage/irritation	: Causes serious eye damage. pH: > 12 (in water)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

Quartz (14808-60-7)

IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

Iron oxide (Fe₂O₃) (1309-37-1)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause respiratory irritation.

Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Cement, portland, chemicals (65997-15-1)	
Specific target organ toxicity – single exposure	May cause respiratory irritation.

Specific target organ toxicity – repeated exposure : Not classified

Quartz (14808-60-7)	
Specific target organ toxicity – repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

Symptoms/effects after eye contact : Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Calcium oxide (1305-78-8)	
LC50 fish 1	1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])

12.2. Persistence and degradability

Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix	
Bioaccumulative potential	Not established.
Calcium oxide (1305-78-8)	
BCF fish 1	(no bioaccumulation)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Longleaf Mortar Cement, Masonry Cement, Colored Mortar Mix, Mortar Mix Stucco Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 15: Regulatory information


15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** This product can expose you to Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Date of issue : 04/03/2019
Revision date : 05/13/2021
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



SDS US (GHS HazCom 2012)_NEXREG_NEW

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.